



CEA Instruments, Inc.

160 Tillman Street

Westwood, N.J. 07675 USA

Phone (201) 967-5660 Fax (201) 967-8450

Website: www.ceainstr.com E-mail: ceainstr@aol.com

CEA 420 SERIES PRICE LIST

REMOTE SENSOR / TRANSMITTER UNITS enclosed in explosion proof housing rated for Class 1, Division 1, Groups B, C, and D hazardous atmospheric areas with 4-20 mA signal output when provided with 12 VDC, 24 VDC, 115VAC, or 220 VAC power (**specify**)

CEA 420 with single housing (For 12VDC power only)	Non display version	\$ 1095 ¹
	With Digital Display	\$ 1295 ¹
CEA 420 with dual housing in series (For 24VDC, 115VAC, or 220VAC power)	Non display version	\$ 1295 ¹
	With Digital Display	\$ 1495 ¹

<u>MODEL</u>	<u>GAS</u>	<u>AVAILABLE RANGES (ppm)²</u>
CEA 421-XX	Ethylene Oxide	0-10, 0-50, 0-100, 0-500, 0-1000
CEA 421-F-XX	Formaldehyde	0-10, 0-50, 0-100, 0-500, 0-1000
CEA 422-XX	Hydrogen Sulfide	0-10, 0-50, 0-100, 0-500, 0-1000
CEA 423-XX	Sulfur Dioxide	0-50, 0-100, 0-250, 0-1000
CEA 424-XX	Carbon Monoxide	0-100, 0-250, 0-500, 0-1000, 0-5000
CEA 425-XX	Ammonia	0-100, 0-250, 0-500, 0-1000, 0-5000
CEA 426-XX	Hydrocarbons (No response to Methane)	0-100, 0-250, 0-500, 0-1000, 0-10,000, 0-100% LEL
CEA 427-XX	Hydrogen	0-1000, 0-5000, 0-20000 (50% LEL), 0-100% LEL
CEA 428-XX	Combustibles (As Methane)	0-1000, 0-50% LEL, 0-100% LEL
CEA 429-XX	Freons (Specify)	0-100, 0-250, 0-500, 0-1000, 0-10,000

¹Freons and SO₂ add \$200

²Other ranges may be available, consult factory

Specify gas, model number, measurement range (XX), power requirements, and then add D for digital display versions when ordering. For example: **Hydrogen CEA 427-1000-12V-D** would be for the 12V version of the CEA 427 Hydrogen 0-1000 ppm with digital display.

SPARES

Replacement Freon or Sulfur Dioxide Sensor (Specify target gas & full range)	\$ 400.00
Other Replacement Sensors (Specify target gas & full range)	\$ 350.00
Calibration / Flow Adapter Cap	\$ 50.00